



NEW, CONTINUATION, DIVISIONAL OR  
CONTINUATION-IN-PART APPLICATION  
UNDER 37 C.F.R. §1.53(b)

Attorney Docket No. 6340-000017  
Express Mail Label No. EL581381107US  
Date October 16, 2000



## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Hon. Commissioner of Patents and Trademarks  
Washington, D. C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R §1.53(b) is a patent application for An Outline Extracting Apparatus; A Method For Extracting An Outline; A Computer Readable Memory Medium Stored With An Outline Extracting Program; and A Computer Readable Memory Medium Stored With An Outline Data

identified by: ☒ First named inventor: Shigeki Morikawa; Taizou Nakamura; Nobuaki Yoshida; Kouichi Motoyama; and Toshihiro Kaneo  
or ☐ Attorney Docket No. (see above)

### 1. Type of Application

☒ This application is a new application.

☐ This application is a ☐ continuation / ☐ divisional / ☐ continuation-in-part of prior application No. \_\_\_\_\_. Amend the specification by inserting before the first line the sentence:

--This is a [continuation/division/continuation-in-part] of United States patent application No. \_\_\_\_, filed \_\_\_\_.--

☐ The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

If for some reason applicant has not requested a sufficient extension of time in the parent application, and/or has not paid a sufficient fee for any necessary response in the parent application and/or for the extension of time necessary to prevent the abandonment of the parent application prior to the filing of this application, please consider this as a Request for an Extension for the required time period and/or authorization to charge our Deposit Account No. 08-0750 for any fee that may be due. THIS FORM IS BEING FILED IN TRIPLICATE: one copy for this application; one copy for use in connection with the Deposit Account (if applicable); and one copy for the above-mentioned parent application (if any extension of time is necessary).

### 2. Contents of Application

a. Specification of 19 pages;

- ☐ A microfiche computer program (Appendix);  
☐ A nucleotide and/or amino acid sequence submission;

☐ Because the enclosed application is in a non-English language, a verified English translation ☐ is enclosed ☐ will be filed.

☐ Cancel original claims \_\_\_\_ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing date purposes.)

b. ☒ Drawings on 7 sheets;

Attorney Docket No. 6340-000017

Express Mail Label No. EL581381107US

Date October 16, 2000

- c. ☒ A signed Oath/Declaration ☐ is enclosed / ☒ will be filed in accordance with 37 C.F.R. §1.53(f).

The enclosed Oath/Declaration is ☐ newly executed / ☐ a copy from a prior application under 37 C.F.R. §1.63(d) / ☐ accompanied by a statement requesting the deletion of person(s) not inventors in the continuing application.

d. **Fees**

<b>FILING FEE</b>	Number	Number		Basic Fee
<b>CALCULATION</b>	Filed	Extra	Rate	\$710.00
Total Claims	7 - 20 =	0 ×	\$18.00 =	-0-
Independent Claims	5 - 3 =	0 ×	\$80.00 =	\$160.00
Multiple Dependent Claim(s) Used			\$270.00 =	-0-
FILING FEE - NON-SMALL ENTITY				\$870.00
FILING FEE - SMALL ENTITY: Reduction by 1/2				
<input type="checkbox"/> Verified Statement under 37 C.F.R. §1.27 is enclosed.				
<input type="checkbox"/> Verified Statement filed in prior application.				
Assignment Recordal Fee (\$40.00)				
37 C.F.R. §1.17(k) Fee (non-English application)				
<b>TOTAL</b>				<b>\$870.00</b>

- ☒ The calculated fees will be paid within the time allotted for completion of the filing requirements.

3. **Priority Information**

- ☐ **Foreign Priority:** Priority based on \_\_\_\_\_ Application No. \_\_\_\_\_, filed \_\_\_\_\_, is claimed.

- ☐ A copy of the above referenced priority document ☐ is enclosed / ☐ will be filed in due course, pursuant to 35 U.S.C. §119(a)-(d).

- ☐ **Provisional Application Priority:** Priority based on United States Provisional Application No. \_\_\_\_\_, filed \_\_\_\_\_, is claimed under 35 U.S.C. §119(e).

Attorney Docket No. 6340-000017

Express Mail Label No. EL581381107US

Date October 16, 2000

4. Other Submissions

☒ A Preliminary Amendment is enclosed.

☐ An Information Disclosure Statement, \_\_\_\_\_ sheets of PTO Form 1449, and \_\_\_\_\_ patent(s)/publications/documents are enclosed.

☐ A power of attorney

☐ is submitted ☐ with the new Oath/Declaration.

☐ is of record in the prior application and ☐ is in the original papers / ☐ a copy is enclosed.

☐ An Assignment of the invention

☐ is enclosed with a cover sheet pursuant to 37 C.F.R. §§3.11, 3.28 and 3.31.

☐ is of record in a prior application. The assignment is to \_\_\_\_\_, and is recorded at Reel \_\_\_\_\_, Frame(s) \_\_\_\_\_.

☐ An Establishment of Assignee's Right To Prosecute Application Under 37 C.F.R. §3.73(b), and Power Of Attorney is enclosed.

☒ An Express Mailing Certificate is enclosed.

☒ Other: Unsigned Declaration & Power of Attorney

Attention is directed to the fact that the correspondence address for this application is:

Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, Michigan 48303  
(248) 641-1600.

Respectfully,

  
Ronald W. Wangerow  
Reg. No. 29,597

Date October 16, 2000  
Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, Michigan 48303  
(248) 641-1600



10-17-00

**HARNES, DICKEY & PIERCE, P.L.C.**  
ATTORNEYS AND COUNSELORS  
P O BOX 828  
BLOOMFIELD HILLS, MICHIGAN 48303  
U S A

TELEPHONE  
(248) 641-1600

TELEFACSIMILE  
(248) 641-0270



Date October 16, 2000

Hon. Commissioner of Patents  
and Trademarks  
Washington, D.C. 20231

Sir:

**EXPRESS MAILING CERTIFICATE**

Applicant: Shigeki Morikawa; Taizou Nakamura; Nobuaki Yoshida; Kouichi  
Motoyama; and Toshihiro Kaneo

Serial No (if any):

For: An Outline Extracting Apparatus; A Method For Extracting An Outline;  
A Computer Readable Memory Medium Stored With An Outline  
Extracting Program; and A Computer Readable Memory Medium  
Stored With An Outline Data


Docket: 6340-000017

Attorney: Ronald W. Wangerow

"Express Mail" Mailing Label Number ..... EL581381107US

Date of Deposit ..... October 16, 2000

I hereby certify and verify that the accompanying Transmittal Letter; 19 page application including at least one claim and an Abstract; Preliminary Amendment; Unsigned Declaration & Power of Attorney; 7 Sheets of Drawings showing Figures 1 through 14 are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" service under 37 C.F.R. 1.10 on the date indicated above and are addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

  
Beverly J. Roberts  
Signature of Person Mailing Document(s)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Attorney Docket No. 6340-000017

Inventors: Morikawa et al )  
Serial No. )  
Filed: )  
For: An Outline Extracting Apparatus; A Method For ) **Preliminary Amendment**  
Extracting An Outline; A Computer Readable )  
Memory Medium Stored With An Outline Extracting )  
Program; and A Computer Readable Memory Medium )  
Stored With An Outline Data )

Hon. Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

**In the Title:**

Please delete the title at page 1, lines 1 through 4, and substitute therefor the title --OUTLINE EXTRACTING APPARATUS AND METHOD AND COMPUTER READABLE MEMORY MEDIUM--.


**In the Specification:**

At page 5, after line 16, please insert the following two paragraphs:

--FIG. 13 illustrates an example of an object for which an outline is to be extracted.

FIG. 14 illustrates the extraction results obtained according to a prior art method.--

Respectfully submitted,

By   
Ronald W. Wangerow  
Reg. No. 29,597

HARNESS, DICKEY & PIERCE, P.L.C.  
P.O. Box 828  
Bloomfield Hills, MI 48303  
(248) 641-1600

Attorney for Applicants

October 16, 2000

An outline extracting apparatus; A method for extracting an outline; A computer readable memory medium stored with an outline extracting program; and A computer readable memory medium stored with an outline data

## BACKGROUND OF THE INVENTION

### Field of the Invention

The present invention relates to an outline extracting apparatus using a CAD (Computer Aided Design) data and a non-contact measuring point data obtained by non-contact measuring an object, a method for extracting an outline, a computer readable memory medium stored with an outline extracting program and a computer readable memory medium stored with an outline data.

### Description of Background Art

Heretofore, there has been used a method for connecting two points in a point group forming a non-contact measuring point data using a straight line as a method for extracting an outline of an object (i.e. an article to be inspected) on a computer by using a non-contact measuring instrument such as a three dimensional scanner. The outline of the object is extracted by the conventional method by obtaining a data of the point group by non-contact measuring an article 30 to be inspected (Fig. 13) using the three dimensional scanner, and connecting two points in the obtained point group by a straight line to form a plurality of triangles.

However, although the side 31 of the article 30 to be inspected is flat surface not having any irregularity, the extracted surface obtained according to the method of the prior art for extracting the outline of the object exhibits undulation as shown by a dashed line "n" in Fig. 14. This is because of the

presence of dispersion in the data of the point group caused by the error of the non-contact measuring instrument. Thus it is very difficult to extract a flat surface by the conventional method.

In addition, an outline 33 formed by the upper surface 32 and the side surface 31 of the article 30 to be inspected as well as an outline 35 formed by the inclined surface 34 and the side surface 31 exhibit a rounded configuration as shown by a dashed line "m" in Fig. 14 which is different from the real outlines 33 and 35 each forming an acute edge. This is because that the data of the point group does not necessarily lie on the outlines 33 and 35. Thus it is very difficult to exactly extract the corner outline having an acute angle by the conventional method.

## SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide an outline extracting apparatus, an outline extracting method, a computer readable memory medium stored with an outline extracting program, and a computer readable memory medium stored with an outline data which can minimize the influence due to the dispersion of the non-contact measuring point data and can also exactly extract the outlines of a flat surface as well as a corner having an acute angle.

According to the present invention of claim 1, there is provided an apparatus for extracting an outline of an object using a CAD data and a non-contact measuring point data comprising an extracted origin data memory means for storing the CAD data and the non-contact measuring point data previously aligned with the CAD data; an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data; and a crossing line extracting means for extracting a



out the surface generation using the analytic surface and the non-contact measuring point data; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

According to the present invention of claim 6, there is provided a computer readable memory medium stored with a program for extracting an outline of an object using a CAD data and a non-contact measuring point data characterized in that said computer readable memory medium is further stored with a program for executing the computer an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a nearby point processing means for extracting the non-contact measuring point data within a predetermined distance from the analytic surface; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data extracted by the nearby point processing means; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

Finally according to the present invention of claim 7, there is provided a computer readable memory medium stored with a data obtained by extracting an analytic surface having a predetermined configuration from the CAD data; carrying out the surface generation using the analytic surface and the non-contact measuring point data; and extracting a crossing line of surfaces generated by the surface generating means as the outline.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the present invention will be described with reference to the accompanied drawings in which;

Fig. 1 is a schematic view showing an arrangement for carrying out the outline extraction of the present invention;

Fig. 2 is a schematic view showing an arrangement of the outline extracting apparatus of the present invention;

Fig. 3 is a flowchart showing the operation of the outline extracting apparatus of the present invention;

Fig. 4 is a perspective view showing an example of the CAD data;

Fig. 5 is a side-elevational view showing the data of the point group of the article to be inspected;

Fig. 6 is an enlarged view of a portion circled by a line VI in Fig. 5;

Fig. 7 is an explanatory view showing the state of the nearby points;

Fig. 8 is a side-elevational view showing an essential portion of Fig. 6 after having carried out the nearby point process thereof;

Fig. 9 is a perspective view showing the state of the surface generation;

Fig. 10 is an explanatory view showing the state of the surface generation;

Fig. 11 is a perspective view showing the state of the crossing line; and

Fig. 12 is a perspective view showing the state of the outline.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in Figs. 1 through 12, an outline extracting apparatus 1 is an apparatus for extracting an outline 26 of an article 2 to be inspected (i.e. an object) using a CAD data 6 generated by a CAD input apparatus 3 and a point group data 7 which is a non-contact measuring point data of the article 2 measured by a point group data input apparatus 4. The outline extracting apparatus 1 is a computer and comprises for example a CPU (Central Processing Unit) 10 for controlling several devices, an input/output controller 11 for connecting a display 14 as well as an input apparatus 15 and the CPU 10, a memory 12 forming a memory medium of data, etc.

The CAD data 6 is a three dimensional graphic data inputted and generated by the CAD input apparatus 3 as well as a design data forming a

base for manufacturing the article 2 to be inspected as shown by an arrow "d" in Fig. 1. That is, the article 2 to be inspected is that manufactured by the CAD data 6. Although the IGES (Initial Graphics Exchange Specification) can be mainly used as a format of the CAD data 6, the format is not limited thereto. The CAD data 6 is transmitted from the CAD input apparatus 3 to the outline extracting apparatus 1 as shown by an arrow "e" in Fig. 1. The transmission of the CAD data 6 along the arrow "e" may be carried out by using any memory medium such as a flexible disk or an MO (Magnet-Optical disk) or by using a communication of serial or parallel system with a cable connecting the CAD input apparatus 3 and the outline extracting apparatus 1. However the method of transmission is not limited to those mentioned.

The point group data 7 is obtained by scanning the outline of the article 2 to be inspected by a three dimensional scanner 13 using a laser beam connected to the point group data input apparatus 4 (i.e. a computer) and by datalizing the information as a group of points. Although the IGES can be mainly used as a format of the point group data 7, the format is not limited thereto. The point group data 7 is transmitted from the point group input apparatus 4 to the outline extracting apparatus 1 as shown by an arrow "f" in Fig. 1. The transmission of the point group data 7 along the arrow "f" may be carried out by using any memory medium such as a flexible disk or an MO or by using a communication of serial or parallel system with a cable connecting the point group input apparatus 4 and the outline extracting apparatus 1. Also the method of transmission is not limited to those mentioned.

The CPU 10 is programmed so that it performs operations shown in Fig. 3. Reference numerals in brackets in following descriptions correspond to those used in the flowchart in Fig. 3. As apparent from the flowchart in Fig. 3, the outline extracting apparatus 1 has functions of analytic surface extracting means (S104) for extracting an analytic surface having a predetermined configuration from the CAD data 6, a nearby point extracting

means for carrying out a nearby point processing on the point group data 7 (S105), a surface generating means (S106) for carrying out the surface generation from the analytic surface and the point group data 7, and a crossing line extracting means (S107) for extracting a crossing line 25 of surfaces generated by the surface generating means as the outline 26.

The memory 12 forms not only an extracted origin data memory means for storing an extracted origin data 5 comprising the CAD data 6 and the point group data 7 but an outline data memory means for storing the extracted outline data 8.

The operation of the outline extracting apparatus 1 of the preferred embodiment of the present invention will be hereinafter described. First of all, the outline extracting apparatus 1 inputs the CAD data 6 transmitted from the CAD input apparatus 3 to the memory 12 (S101). Then, the outline extracting apparatus 1 inputs the point group data 7 transmitted from the point group data input apparatus 4 to the memory 12 (S102) and aligns the CAD data 6 and the point group data 7 (S103). Owing to this alignment, the CAD data 6 and the point group data 7 are superimposed each other as shown in Figs. 5 and 6. Although it is described that the alignment operation is carried out as one operation of the outline extracting apparatus 1, it may be possible to carry out the alignment operation by other apparatus than the outline extracting apparatus 1 and to input the CAD data 6 and the point group data 7 as a unit to the outline extracting apparatus 1.

Then the outline extracting apparatus 1 extracts from the CAD data 6 an analytic surface necessary for extracting the outline 26 (S104). The configuration of the analytical surface to be extracted is for example a plane, a cylindrical surface, a conical surface, a spherical surface etc.. The extracting method of the analytical surface will be hereinafter described as to an example in a case that the analytical surface is an analytical plane 6a.

First of all, informations of lateral and vertical isoparametric curves are

obtained from the NURBS (Non Uniform Rational B-Spline) curved surfaces which are a plurality of free-curved surfaces contained in the CAD data 6. A surface in which both the lateral isoparametric curve (hereinafter referred to “Cu”) and the vertical isoparametric curve (hereinafter referred to “Cv”) are parallel straight line group is recognized as the plane i.e. the analytic plane 6a. The informations as to the Cu and the Cv are substituted for a following plane formula (“Formula 1”) to find a three dimensional vector  $P_0$  representing the position of the analytic plane 6a, a three dimensional vector  $U$  representing the lateral direction of the analytical plane 6a, and a three dimensional vector  $V$  representing the vertical direction of the analytical plane 6a. In the formula 1, characters “u” and “v” are scalar values each representing a length. A plane in the extracted analytic planes having a micro width to which the point group data 7 is spanned is deleted and the remained planes are used for the outline extraction.

【Formula 1】

$$\overline{P}(u, v) = \overline{P}_0 + u \times \overline{U} + v \times \overline{V}$$

When one of Cv and Cu is the parallel straight line group and the other is a circle group each circle having an equal radius and a coaxial center, it is regarded as the cylindrical surface and the informations as to Cu and Cv are substituted for a following Formula 2 of the cylindrical surface to find three dimensional vectors  $P_0$ ,  $U$  and  $V$ , a three dimensional vector  $N$  representing the height direction of the analytical cylindrical surface 6b, and a radius “r” of the analytical cylindrical surface 6b. In Formula 2, characters “ $\theta$ ” and “h” are scalar values representing the depression angle and the height respectively.

【Formula 2】

$$\overline{P}(\theta, h) = \overline{P}_0 + h \times \overline{N} + r \times \overline{U} \times \cos \theta + r \times \overline{V} \times \sin \theta$$

In addition, when one of Cv and Cu is the straight line group and the other is a circle group each circle having a gradually varied radius and a coaxial center, it is regarded as the conical surface and the informations as to

Cu and Cv are substituted for a following Formula 3 of the conical surface to find three dimensional vectors P<sub>0</sub>, U, V and N, and an elevation angle “ $\phi$ ” of the analytical conical surface.

【Formula 3】

$$\overline{P}(\theta, h) = \overline{P}_0 + h \times \overline{N} + h \times \overline{N} \times \tan \phi \times \overline{U} \times \cos \theta + h \times \overline{N} \times \tan \phi \times \overline{V} \times \sin \theta$$

Furthermore, when one of Cv and Cu is the circle group each having an equal radius and the other is a circle group each circle having a gradually varied radius and a coaxial center, it is regarded as the spherical surface and the informations as to Cu and Cv are substituted for a following Formula 4 of the spherical surface to find three dimensional vectors P<sub>0</sub>, U, V and N, and an radius “r”.

【Formula 4】

$$\overline{P}(\theta, h) = \overline{P}_0 + r \times \cos \phi \times (\overline{U} \times \cos \theta + \overline{V} \times \sin \theta) + r \times \overline{N} \times \sin \phi$$

Then the nearby point processing is carried out (S105). In the nearby point process, a point 20 nearest to a certain analytical plane is found by the shortest distance calculation and the extracted point 20 is positioned on the point group data 7 forming its analytical plane. Then the point group data 7 is divided to several small groups A, B, C... in accordance with the distances from the analytical plane and based upon a pre-inputted threshold as shown in Fig. 7. The groups away from the analytical plane are deleted from the point group data 7 at need. Fig. 8 shows a condition in which only the group A has been remained and the other group B and C have been deleted. From this work, it is possible to remove the dispersion due to the error of the three dimensional scanner 13 included in the point group data 7. If the nearby point process is not be carried out, it is carried out in the following mentioned surface generating means prior to the surface generation.

Then the surface generation is carried out in accordance with the information of the analytical surface and the point group data 7 positioned on the analytical surface (S106). Again, an analytical plane 6a in which the

analytical surface is a flat surface will be hereinafter described. Since the point group data 7 positioned on the analytical plane 6a is strictly a point group forming the plane, it is possible to unconditionally find each value shown in a following Formula 5 of plane using this point group data 7.

【Formula 5】

$$\overline{P}(u, v) = \overline{P}_1 + u \times \overline{U} + v \times \overline{V}$$

Concretely, the three dimensional vector  $P_1$  representing the position of the plane which is an information of the asymptotic surface having a highest balance for example of  $(h_1+h_3+h_5)$  and  $(h_2+h_4)$  and the three dimensional vector  $U$ -outer product-three dimensional vector  $V$  are found by adding a calculation of the least square method on the information of each point 20 as shown in Fig. 10. Then the three dimensional vector  $U$  and the three dimensional vector  $V$  are found by solving the three dimensional vector  $U$ -outer product-three dimensional vector  $V$  in accordance with that the condition of the three dimensional vector  $U$  and the three dimensional vector  $V$  being orthogonal is satisfied. With the result of which the plane formula of the generated plane 22 is completed and thus the plane 22 can be generated.

Since the point group data 7 positioned on the analytical cylinder 6b is strictly a point group forming the cylindrical surface when the analytical surface is the analytical cylindrical surface 6b, it is possible to unconditionally find each value shown in a following Formula 6 of cylindrical surface using this point group data 7.

【Formula 6】

$$\overline{P}(\theta, h) = \overline{P}_1 + h \times \overline{N} + r \times \overline{U} \times \cos \theta + r \times \overline{V} \times \sin \theta$$

Concretely, the three dimensional vectors  $P_1$  and  $N$  and the radius “ $r$ ” are found by using the least square method similarly to the generated plane 22. The three dimensional vector  $U$  and the three dimensional vector  $V$  are found from the value of the three dimensional vector  $N$  by solving the formula 6 in accordance with that the condition of the three dimensional vector  $U$  and

the three dimensional vector V being orthogonal is satisfied. With the result of which the formula of the generated cylindrical surface 23 is completed and thus the cylindrical surface 23 can be generated.

Since the point group data 7 positioned on the analytical conical surface is strictly a point group forming the conical surface when the analytical surface is the analytical conical surface, it is possible to unconditionally find each value shown in a following Formula 7 of conical surface using this point group data 7.

【Formula 7】

$$\overline{P}(\theta, h) = \overline{P}_1 + h \times \overline{N} + h \times \overline{N} \times \tan \phi \times \overline{U} \times \cos \theta + h \times \overline{N} \times \tan \phi \times \overline{V} \times \sin \theta$$

Concretely, the three dimensional vectors  $P_1$  and  $N$  and the elevation angle “ $\phi$ ” are found by using the least square method similarly to the generated plane 22. The three dimensional vector  $U$  and the three dimensional vector  $V$  are found from the value of the three dimensional vector  $N$  by solving the formula 7 in accordance with that the condition of the three dimensional vector  $U$  and the three dimensional vector  $V$  being orthogonal is satisfied.

Since the point group data 7 positioned on the analytical spherical surface is strictly a point group forming the spherical surface when the analytical surface is the analytical spherical surface, it is possible to unconditionally find each value shown in a following Formula 8 of spherical surface using this point group data 7.

【Formula 8】

$$\overline{P}(\theta, h) = \overline{P}_1 + r \times \cos \phi \times (\overline{U} \times \cos \theta + \overline{V} \times \sin \theta) + r \times \overline{N} \times \sin \phi$$

Concretely, the three dimensional vectors  $P_1$  and the radius “ $r$ ” are found by using the least square method similarly to the generated plane 22.

Then the crossing line 25 formed by the generated surfaces is found and the crossing line 25 is extracted as an outline 26 (S107). Concretely, the crossing line 25 formed by the generated plane 22 and the generated



According to the preferred embodiment of the present invention, the CAD data 6 is generated by a computer other than the outline extracting apparatus 1 and transmitted to the outline extracting apparatus 1. However, it is possible to carry out both the generation of the CAD data 6 and the extraction of the outline by a same computer.

Also it is possible to obtain the point group data 7 by directly connecting the non-contact measuring instrument i.e. the three dimensional scanner 13 to the outline extracting apparatus 1 as shown by a dotted line in Fig. 2. In addition it is possible to generate the CAD data 6 by the outline extracting apparatus 1 to which the three dimensional scanner 13 is connected and thus to realize the outline extracting apparatus 1 having both functions of the CAD input apparatus 3 and the point group data input apparatus 4.

In the preferred embodiment of the present invention, it has been described that the outline extracting apparatus 1 is just as a dedicated apparatus for extracting an outline. However, it is possible to have a computer carry out a more exact outline extraction having less influence of the dispersion of the point group data 7 by storing in a computer readable memory medium a program for executing the computer the analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data 6, the nearby point processing means for extracting the point group data 7 within a predetermined distance from the analytic surface, the surface generating means for carrying out the surface generation using the analytic surface and the point group data 7 extracted by the nearby point processing means, and the crossing line extracting means for extracting a crossing line 25 of surfaces generated by the surface generating means as the outline 26.

According to the present invention of claim 1, since the apparatus for extracting an outline of an object has the analytic surface extracting means for extracting an analytic surface having a predetermined configuration from





data, and extracting a crossing line of surfaces generated by the surface generating means as the outline, it is possible to have the extracted external appearance of an object formed by smooth surfaces generated by the surface generating means, and also to exactly extract the outline less influenced by the dispersion of the non-contact point group data. In addition, it is possible to exactly extract the outline of a corner having an acute angle because of using the crossing line of surfaces as the outline.

WHAT IS CLAIMED IS:

1. An apparatus for extracting an outline of an object using a CAD data and a non-contact measuring point data comprising an extracted origin data memory means for storing the CAD data and the non-contact measuring point data previously aligned with the CAD data; an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

2. An apparatus of claim 1 wherein further comprising a nearby point extracting means for extracting the non-contact measuring point data within a predetermined distance from the analytic surface and for using the extracted non-contact measuring point data as the non-contact measuring point data used in the surface generating means.

3. A method for extracting an outline of an object using a CAD data and a non-contact measuring point data comprising steps of inputting the CAD data and the non-contact measuring point data previously aligned with the CAD data; extracting an analytic surface having a predetermined configuration from the CAD data; carrying out the surface generation using the analytic surface and the non-contact measuring point data; and extracting a crossing line of surfaces generated by the surface generating means as the outline.

4. A method of claim 3 wherein further comprising steps of carrying out a nearby point process for extracting the non-contact measuring point data within a predetermined distance from the analytic surface and also carrying out the surface generation by using the nearby point processed non-contact measuring point data and the analytic surface.

5. A computer readable memory medium stored with a program for extracting an outline of an object using a CAD data and a non-contact measuring point data characterized in that said computer readable memory medium is further stored with a program for executing the computer an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

6. A computer readable memory medium stored with a program for extracting an outline of an object using a CAD data and a non-contact measuring point data characterized in that said computer readable memory medium is further stored with a program for executing the computer an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a nearby point processing means for extracting the non-contact measuring point data within a predetermined distance from the analytic surface; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data extracted by the nearby point processing means; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

7. A computer readable memory medium stored with a data obtained by extracting an analytic surface having a predetermined configuration from the CAD data; carrying out the surface generation using the analytic surface and the non-contact measuring point data; and extracting a crossing line of surfaces generated by the surface generating means as the outline.

## ABSTRACT OF THE DISCLOSURE

The present invention provide an outline extracting apparatus, a method for extracting an outline, a computer readable memory medium stored with an outline extracting program and a computer readable memory medium stored with an outline data which can exactly extract the outline less influenced by the dispersion of the non-contact point group data and also can exactly extract the outline of a corner having an acute angle.

The present invention is characterized in that it comprises an extracted origin data memory means for storing the CAD data and the non-contact measuring point data previously aligned with the CAD data; an analytic surface extracting means for extracting an analytic surface having a predetermined configuration from the CAD data; a surface generating means for carrying out the surface generation using the analytic surface and the non-contact measuring point data; and a crossing line extracting means for extracting a crossing line of surfaces generated by the surface generating means as the outline.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13





Fig. 14



PRIOR ART

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

### Japanese Language Declaration

#### 日本語宣言書

下の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

See Attachment 1

See Attachment 2

上記発明の明細書（下記の欄でX印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
（該当する場合） \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

### Prior Foreign Application(s)

外国での先行出願  
Hei 11-108885

Japan

(Number)  
(番号)

(Country)  
(国名)

(Number)  
(番号)

(Country)  
(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

16 April 1999

(Day/Month/Year Filed)  
(出願年月日)

☒

(Day/Month/Year Filed)  
(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の  
手続きを米特許商標局に対して遂行する弁理士または代理人  
として、下記の者を指名いたします。(弁護士、または代理  
人の氏名及び登録番号を明記のこと)

Ronald W. Wangerow 29,597

**POWER OF ATTORNEY:** As a **named inventor**, I hereby appoint  
the following **attorney(s) and/or agent(s)** to prosecute this  
application and transact all business in the Patent and Trademark  
Office connected therewith (*list name and registration number*)

Ronald W. Wangerow 29,597

### 書類送付先

Ronald W. Wangerow, Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, MI 48303 u.s.a.

### Send Correspondence to:

Ronald W. Wangerow, Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, MI 48303 u.s.a.

### 直接電話連絡先： (名前及び電話番号)

Ronald W. Wangerow

248-641-1600

### Direct Telephone Calls to: (name and telephone number)

Ronald W. Wangerow

248-641-1600

### 唯一または第 発明者名

Shigeki Morikawa

### Full name of sole or first inventor

Shigeki Morikawa

発明者の署名 日付

Inventor's signature

Date

住所 Shizuoka-ken Japan

Residence Shizuoka-ken Japan

### 国籍

Japanese

### Citizenship

Japanese

私書箱 c/o 111-2 Itaya-machi

Hamamatsu-shi

Shizuoka-ken Japan

Post Office Address c/o 111-2 Itaya-machi

Hamamatsu-shi

Shizuoka-ken Japan

### 第二共同発明者

Taizou Nakamura

### Full name of second joint inventor if any

Taizou Nakamura

第二共同発明者 日付

Second inventor's signature

Date

住所 Shizuoka-ken Japan

Residence Shizuoka-ken Japan

### 国籍

Japanese

### Citizenship

Japanese

私書箱 c/o 111-2 Itaya-machi

Hamamatsu-shi

Shizuoka-ken Japan

Post Office Address c/o 111-2 Itaya-machi

Hamamatsu-shi

Shizuoka-ken Japan

(第三以降の共同発明者についても同様に記載し、署名をす  
ること)

(Supply similar information and signature for third and subsequent  
joint inventors.)

Please type a plus sign (+) inside this box → ☐

PTO/SB/02A (3-97)  
Approved for use through 9/30/98. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

+

## DECLARATION

## ADDITIONAL INVENTOR(S) Supplemental Sheet Page 1 of 1

<b>Name of Additional Joint Inventor, if any:</b>		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any])				Family Name or Surname			
Nobuaki				Yoshida			
Inventor's Signature						Date	
Residence: City	Osaka-fu	State		Country	Japan	Citizenship	Japanese
Post Office Address	c/o 1006 Oaza Kadoma						
Post Office Address	Kadoma-shi						
City	Osaka-fu	State		ZIP		Country	Japan
<b>Name of Additional Joint Inventor, if any:</b>		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any])				Family Name or Surname			
Kouichi				Motoyama			
Inventor's Signature						Date	
Residence: City	Osaka-fu	State		Country	Japan	Citizenship	Japanese
Post Office Address	c/o 1006 Oaza Kadoma						
Post Office Address	Kadoma-shi						
City	Osaka-fu	State		ZIP		Country	Japan
<b>Name of Additional Joint Inventor, if any:</b>		<input type="checkbox"/> A petition has been filed for this unsigned inventor					
Given Name (first and middle [if any])				Family Name or Surname			
Toshihiro				Kaneo			
Inventor's Signature						Date	
Residence: City	Osaka-fu	State		Country	Japan	Citizenship	Japanese
Post Office Address	c/o 1006 Oaza Kadoma						
Post Office Address	Kadoma-shi						
City	Osaka-fu	State		ZIP		Country	Japan

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231

+

